

IR bullet camera(fix lens)



- ✚ 3-Axis bracket
- ✚ Weatherproof Rate: IP66
- ✚ IR LED: 30EA ϕ 5
- ✚ Lens: 3.6/6mm

		FST-45M820-C	FST-45M620-C	FST-45M720-C
CAMERA	Image Sensor	1/3" DIS		
	Signal System	PAL/NTSC		
	Effective Pixels	720(H)X480(V)	728(H)X488(V)	976(H)X496(V)
	Min Illumination	0.1Lux @ (F1.2,AGC ON),0 Lux with IR		
		0.14Lux @ (F1.4,AGC ON),0 Lux with IR		
	Shutter Time	1/50(1/60)s to 1/100,000s		
	Lens	3.6/6MM @ F1.4		
	Lens Mount	ϕ 12		
	Day & Night	IR cut filter with auto switch		
	Horizontal Resolution	600TVL	700TVL	1000TVL
	Synchronization	Internal Synchronization		
	Video Output	1Vp-p Composite Output (75 Ω /BNC)		
	S/N Ratio	More than 62 dB		
	BLC	On		
	OSD	WDR	D-WDR	
Back Light		ON/OFF/HLC		--
Motion Detection		ON/OFF		--
Privacy		ON/OFF		--
Language		English/Chinese/Spanish/Russian/Japanese/Dutch/French/Portuguese		--
GENERAL	Operating Conditions	-40 °C - 60 °C (-40 °F - 140 °F)		
		Humidity 90% or less (non-condensing)		
	Power Supply	12 V DC \pm 10%		
	Power Consumption	Max. 4 W(Max. 5 W with IR cut filter on)		
	Weather Proof	IP66		
	IR Range	Approx 25 to 30 meters		
Weight	300G			