

Outdoor dome camera



- ✚ High Resolution
- ✚ OSD menu
- ✚ 2D-NR
- ✚ Built-in IR LEDs (36pcs EA)
- ✚ Built-in 2.8-12mm varifocal lens
- ✚ Weatherproof rating: IP66

| FST-626720-S | | |
|----------------------|-----------------------------|--|
| Image Sensor | 1/3" SONY CCD (960H) | |
| TV system | PAL/NTSC | |
| Total Pixel | 976(H) x 494(V) NTSC | |
| | 976(H) x 582(V) PAL | |
| Horizontal Res. | 700TVL | |
| Video Output | 1.0V p-p (75 ohm, compiste) | |
| Scanning System | 2:1 Interlace | |
| Minimum Illumination | Color: 0.1Lux@F1.2; | |
| | B/W: 0.08Lux@F1.2 | |
| | 0Lux(IR ON) | |
| IR LED | 36EA ϕ 5 (850nm 60°) | |
| S/N Ratio | >50 dB (AGC OFF) | |
| Lens | 2.8-12mm | |
| DNR | 2-DNR | |
| OSD | WDR | D-WDR |
| | Back Light | OFF/BLC/HLC |
| | Motion Detection | ON/OFF |
| | Privacy | ON/OFF |
| | Language | English/Chinese/Spanish/Russian/Japanese/Dutch/French/Portuguese |
| Weatherproof Rating | IP66 | |
| Power Voltage | DC12V | |
| Operation Temp. | -10°C~50°C | |
| Net weight | 650g | |