

## Outdoor dome camera



- ✚ Vandalproof Dome
- ✚ Weatherproof Rate: IP65
- ✚ IR LED: 36pcs EA  $\phi$  5
- ✚ Lens: 2.8-12mm
- ✚ Lens and Focus adjustable from outside
- ✚ 3 Axis bracket

		FST-626M620-C	FST-626M720-C	FST-626M120-C
CAMERA	Image Sensor	1/3" DIS		
	Signal System	PAL/NTSC		
	Effective Pixels	720(H)X480(V)	728(H)X488(V)	976(H)X496(V)
	Min Illumination	0.1Lux @ (F1.2,AGC ON),0 Lux with IR		
		0.14Lux @ (F1.4,AGC ON),0 Lux with IR		
	Shutter Time	1/50(1/60)s to 1/100,000s		
	Lens	2.8-12 mm/4-9MM @ F1.4		
	Lens Mount	$\phi$ 14		
	Day & Night	IR cut filter with auto switch		
	Horizontal Resolution	600TVL	700 TVL	1000TVL
	Synchronization	Internal Synchronization		
	Video Output	1Vp-p Composite Output (75 $\Omega$ /BNC)		
	S/N Ratio	More than 62 dB		
	BLC	On		
	OSD	WDR	D-WDR	
Back Light		ON/OFF/HLC		--
Motion Detection		ON/OFF		--
Privacy		ON/OFF		--
Language		English/Chinese/Spanish/Russian/Japanese/Dutch/French/Portuguese		--
GENERAL	Operating Conditions	-40 °C - 60 °C (-40 °F - 140 °F)		
		Humidity 90% or less (non-condensing)		
	Power Supply	12 V DC $\pm$ 10%		
	Power Consumption	Max. 4 W(Max. 5 W with IR cut filter on)		
	Weather Proof	IP66		
	IR Range	Approx 30 to 40 meters		
Weight	650G			