

IR bullet camera(fix lens)



- ✚ Hi-Res. IR-CUT
- ✚ Weatherproof Rate: IP66
- ✚ IR LED: 48EA \$ 5
- ✚ Lens: 6/8/12/16mm CS mount
- ✚ POE option

	FST-781320	FST-78320
Camera		
Image Sensor:	1/4" DIS	1/27" DIS
Min. Illumination:	0.07Lux @ (F1.2, AGC ON) ,0 Lux with IR	
Shutter time:	1/25(1/30) s to 1/100,000 s	
Lens:	6/8/12/16mm(2MP)	6/.8/12/16mm(3MP)
Day& Night:	IR cut filter with auto switch	
Wide Dynamic Range:	Digital WDR	
Digital noise reduction:	3D DNR	
Image		
Max. Image Resolution:	1280x720	1920x1080
Frame Rate:	50Hz: 25fps /60Hz: 30fps	50Hz/60Hz: 25fps; CBR/VBR adjustable
Video Compression:	H.264	
Bit Rate:	32 Kbps ~ 16 Mbps	
Dual Stream:	Yes	
Image Settings:	Rotate mode, Saturation, Brightness, Contrast adjustable by VMS or web browser	
BLC:	zone configurable	
Network		
Motion Detection	4 zones (sensitivity from 1~100)	
Alarm Trigger	Snapshot image upload via FTP; Notification via email	
Protocols:	TCP/IP,HTTP,TCP,ICMP,UDP,ARP,IGMP,SMTP,FTP,DHCP,DNS, DDNS,NTP,UPNP,RTSP	
System Compatibility:	ONVIF 2.4.2	
Communication Interface:	1 RJ45 10M / 100M Ethernet interface	



General	
Operating Conditions:	-30 °C ~ 60 °C (-22 °F ~ 140 °F)
	Humidity 95% or less (non-condensing)
Power Supply:	12 VDC \pm 10%
Power Consumption:	Max. 5 W (Max. 7 W with IR cut filter on)
Weather Proof:	IP66
IR Range:	Up to 35m (48EA)
Weight:	300g