# ForeSight

# AHD 1 SATA 4ch Hybrid HD DVR

- Support AHD series front-end real-time encoding
- Support VGA HD output
- Support Cloud technology, easy to achieve a variety of network penetration, one step to remote monitoring, getting rid of various complicated network settings, easy and simple to operate;
- Support various mobile monitoring:（IOS, Windows Mobile, BlackBerry, Symbian, Android）
- Support multiple web browsers（IE,Chrome,Firefox,Safari）
- Support more than 20 languages, no nation boundaries
- Perfect protection circuit, unique triple watchdog function
- Supporting web, CMS, center platform management software MYEYE, provide SDK development.

| FST-A4K5 | | |
|---|---|---|
| **System** | Main processor | Huawei Hi 3520D |
| **Video** | video compression | H.264(High Profile)； |
| | Encode | 4*AHD |
| | Decode | 1*AHD |
| | Multiode | Only Analog：4*AHD；4*AHD |
| | input | Analog+IP：2*720P (analog) +2*720P （IP） |
| | | IP：4*720P；8*1080P； |
| | | 4*1080P；1*1080P；8*720P； |
| **Audio** | Audio compression | G.711A |
| | Intercom | support |
| **Recording and Playback** | Record mode | Manual>alarm>motion detection>timing |
| | Playback Channels | 4 (pure local input mode) |
| **Storage and backup** | Space occupation | 960H：12~20G/ day*channel |
| | | 720P：20G~30G/ day*channel |
| | | audio：691.2M/ day*channel |
| | Backup mode | Network backup、USB HDD, USB writer、SATA writer |
| **Interface** | Video input | 4 BNC |
| | Video output | 1ch VGA |
| | Audio input | 1ch RCA |
| | Audio output | 1ch RCA |
| | Alarm input | NO |
| | Alarm output | NO |
| | Network interface | RJ45 10M/100M Adaptive Ethernet port |

| | PTZ control | NO |
|---|---|---|
| | USB | 2 USB ports |
| | Hard disk | 1 SATA port（Each maximum support 4T ） |
| | Wireless | No |
| **Other** | Power | 12V/2A |
| | dimension | 255mm(length)* 225mm(width)* 45mm(height) |