

2 SATA 16ch Analog HD DVR



- + Support ADH-L series front-end non-real-time encoding;
- + Support VGA, HDMI HD output;
- + Support XM Cloud technology, easy to achieve a variety of network penetration, one step to remote monitoring, getting rid of various complicated network settings, easy and simple to operate;
- + Support various mobile monitoring: (IOS, Windows Mobile, BlackBerry, Symbian, Android) .
- + Support multiple web browsers (IE、Chrome、Firefox、Safari);
- + Support more than 20 languages (English、Finnish、French、German、Greek、Italian、Japanese、Polish、Portuguese、Russian、Spanish、Thai、Chinese、Traditional Chinese、Turkish、etc.), no nation boundaries;
- + perfect protection circuit, unique triple watchdog function
- + Supporting web, CMS, center platform management software MYEYE, provide SDK development.

FST-AH162K5		
System	Main processor	Huawei Hass 3521
Video	video compression	H.264(High Profile);
	Encode	16* AHD-L @12fps
	Decode	4* AHD-L @12fps
	Multi-mode input	Pure Analog: 16* AHD-L ; 16*D1; 16*CIF; 4*D1+12*CIF;Mixed: 4*D1 (Analog) +1*1080P (Network) +3*720P (Network) ;Pure Network: 2*1080P; 2*720P; 8*720P; 1*1080P+1*720P+6*D1;16*D1
Audio	Audio compression	G.711A
	Intercom	support
Recording and Playback	Record mode	Manual>alarm>motion detection>timing
	Playback Channels	4 (pure local input mode)
Storage and backup	Space occupation	960H: 12~20G/ day*channel
		720P: 20G~30G/ day*channel
		audio: 691.2M/ day*channel



	Backup mode	Network backup、USB HDD, USB writer、SATA writer
Interface	Video input	16 BNC
	Video output	1ch VGA,1ch HDMI
	Audio input	2ch RCA
	Audio output	1ch RCA
	Alarm input	No
	Alarm output	No
	Network interface	RJ45 10M/100M Adaptive Ethernet port
	PTZ control	RS485; support multiple PTZ protocols
	USB	2 USB ports
	Hard disk	2 SATA (Each maximum support 4T)
Wireless	3G、WIFI(expand via USB)	
Other	Power	12V/2A
	dimension	255mm(length)* 225mm(width)* 45mm(height)