

## 4 SATA 16ch Analog HD DVR



- + Support AHD-M series front-end real-time encoding;
- + Support VGA, HDMI HD output;
- + Support XM Cloud technology, easy to achieve a variety of network penetration, one step to remote monitoring, getting rid of various complicated network settings, easy and simple to operate;
- + Support various mobile monitoring: (IOS, Windows Mobile, BlackBerry, Symbian, Android) .
- + Support multiple web browsers (IE,Chrome,Firefox,Safari) ;
- + Support more than 20 languages, no nation boundaries;
- + perfect protection circuit, unique triple watchdog function
- + Supporting web, CMS, center platform management software MYEYE, provide SDK development.

### FST-AH164K5

FST-AH164K5		
System	Main processor	Huawei Hi 3531
Video	video compression	H.264(High Profile) ;
	Encode	16*AHD-M
	Decode	1*AHD-M
	Multi-mode input	Pure Analog : 16*AHD-M; 8*AHD-M; 16*AHD-L; Mixed : 4*AHD-M(analog) +4*720P ( network ) ; Pure Network : 1*1080P+8*720P ; 4*1080P ; 20*960H ;
Audio	Audio compression	G.711A
	Intercom	support
Recording and Playback	Record mode	Manual>alarm>motion detection>timing
	Playback Channels	4 (pure local input mode)
Storage and backup	Space occupation	960H : 12~20G/ day*channel
		720P : ~20G/ day*channel
		audio : 691.2M/ day*channel
	Backup mode	Network backup · USB HDD, USB writer · SATA writer
Interface	Video input	16 BNC
	Video output	1ch VGA, 1ch HDMI
	Audio input	16ch RCA
	Audio output	1ch RCA
	Alarm input	16
	Alarm output	4
	Network interface	RJ45 10M/100M Adaptive Ethernet port



# ForeSight

Email: [sales@foresight-systech.com](mailto:sales@foresight-systech.com)  
[www.foresight-systech.com](http://www.foresight-systech.com)

	PTZ control	RS485 ; support multiple PTZ protocols
	USB	2 USB ports
	Hard disk	4 SATA ( Each maximum support 4T )
	Wireless	3G 、WIFI(expand via USB)
Other	Power	12V/6A
	dimension	440mm(length)* 345mm(width)* 60mm(height)