

# AHD 1 SATA 4ch Hybrid HD DVR



- Support AHD (Analog High definition) cameras, non real-time recording
- Support VGA、TV output
- Support Cloud technology, easy to achieve a variety of network penetration, alarm information will be pushed to mobile
- Support various mobile monitoring: (IOS, Windows Mobile, BlackBerry, Symbian, Android) .
- Support multiple web browsers (IE,Chrome,Firefox,Safari) ;
- Support more than 20 languages (English,Finnish, French, German, Greek, Italian, Japanese, Polish, Portuguese, Russian, Spanish, Thai, Chinese, Traditional Chinese, Turkish, etc.) , no nation boundaries
- Perfect protection circuit, unique triple watchdog function
- Supporting web, CMS, center platform management software, provide SDK development

FST-AH4K5		
System	Main processor	Huawei XM610
Video	video compression	H.264(High Profile)
	Record	4*D1 real time/4*AHD-L*12fps
	Playback	4*D1 real time/4*AHD-L*12fps
	Multi-mode input	Only Analog : 4*AHD ( Analog ) ; 4*D1 ( Analog ) ; Analog+IP : 2*D1( Analog ) +1*720P ( IP ) +1*960H(IP) ; Only IP : 4*1080P ( IP ) ; 1*1080P ( IP ) 8*D1 ( IP )
Audio	Audio compression	G.711A
	Bidirection talk	Support
Recording and Playback	Record mode	Manual>alarm>motion detection>timing
	Playback Channels	4ch ( Only Analog mode )
Storage and backup Interface	Space occupation	960H : 12~20G/ day*channel
		720P : 20G~30G/ day*channel
		Audio : 691.2M/ day*channel
	Backup mode	Network ·USB HDD, USB writer ·SATA writer
	Video input	4ch BNC
	Video output	1ch VGA · 1ch TV
	Audio input	1ch RCA
	Audio output	1ch RCA
	Alarm input	NO
	Alarm output	NO
	Network interface	RJ45 10M/100M Adaptive Ethernet



Email: sales@foresight-systech.com  
www.foresight-systech.com

		port
PTZ control		NO
USB		2*USB ports
Hard disk		1 SATA ( Each maximum support 4T )
Wireless		NO
Other	Power	12V/2A
	dimension	255mm(L)*225(W)*45mm(H)