

2 SATA 8ch Analog HD DVR



- + Support AHD series front-end real-time encoding;
- + Support VGA, HDMI 1080P full HD output;
- + Support Cloud technology, easy to achieve a variety of network penetration, one step to remote monitoring, getting rid of various complicated network settings, easy and simple to operate;
- + Support various mobile monitoring: (IOS, Windows Mobile, BlackBerry, Symbian, Android) .
- + Support multiple web browsers (IE、Chrome、Firefox、Safari);
- + Support more than 20 languages (English、Finnish、French、German、Greek、Italian、Japanese、Polish、Portuguese、Russian、Spanish、Thai、Chinese、Traditional Chinese、Turkish、etc.), no nation boundaries;
- + perfect protection circuit, unique triple watchdog function
- + Supporting web, CMS, center platform management software MYEYE, provide SDK development.

FST-AH872K5		
System	Main processor	Huawei Hass 3531
Video	video compression	H.264(High Profile) ;
	Encode	8*720P real-time
	Decode	8*720P real-time
	Multi-mode input	Pure Analog : 8*720P; 8*AHD; Mixed : 4*720P (Analog)+4*720P (Network); Pure Network : 1*1080P+8*720P; 4*1080P; 20*960H
Audio	Audio compression	G.711A
	Intercom	support
Recording and Playback	Record mode	Manual>alarm>motion detection>timing
	Playback Channels	8 (pure local input mode)
Storage and backup	Space occupation	960H : 12~20G/ day*channel
		720P : 20G~30G/ day*channel
		audio : 691.2M/ day*channel
	Backup mode	Network backup 、USB HDD, USB writer 、SATA writer
Interface	Video input	8 BNC
	Video output	1ch VGA,1ch HDMI
	Audio input	6ch RCA



	Audio output	1ch RCA
	Alarm input	4
	Alarm output	1
	Network interface	RJ45 10M/100M Adaptive Ethernet port
	PTZ control	RS485 ; support multiple PTZ protocols
	USB	2USB ports
	Hard disk	2 SATA (Each maximum support 4T)
	Wireless	3G 、WIFI(expand via USB)
Other	Power	12V/4A
	dimension	350mm(L)* 295mm(W)* 45mm(H)