

AHD 1 SATA 8ch Analog HD DVR



- Support AHD Cameras front-end real-time encoding;
- Support VGA, HDMI 1080P full HD output;
- Support Cloud technology, easy to achieve a variety of network penetration, one step to remote monitoring, getting rid of various complicated network settings, easy and simple to operate;
- ♣ Support various mobile monitoring: (IOS, Windows Mobile, BlackBerry, Symbian, Android).
- ♣ Support multiple web browsers (IE、Chrome、Firefox、Safari);
- Support more than 20 languages (English Finnish, French, German, Greek, Italian, Japanese, Polish, Portuguese, Russian, Spanish, Thai, Chinese, Traditional Chinese, Turkish, etc.), no nation boundaries
- ♣ Perfect protection circuit, unique triple watchdog function
- Supporting web, CMS, center platform management software MYEYE, provide SDK development.

FST-AH87K5		
System	Main processor	Huawei Hass 3531
Video	video compression	H.264(High Profile);
	Encode	8*720P real-time
	Decode	8*720P real-time
	Multi-mode	Pure Analog: 8*720P; 8*AHD
	input	Mixed: 4*720P (Analog) +4*720P (Network);
		Pure Network: 1*1080P+8*720P; 4*1080P; 20*960H
Audio	Audio compression	G.711A
	Intercom	support
Recording and	Record mode	Manual>alarm>motion detection>timing
Playback	Playback Channels	8*720P@25fps)
Storage and backup	Space occupation	960H: 12~20G/ day*channel
		720P: 20G~30G/ day*channel
		audio: 691.2M/ day*channel
	Backup mode	Network backup, USB HDD, USB writer, SATA
		writer
Interface	Video input	8 BNC
	Video output	1ch VGA,1ch HDMI
	Audio input	2ch RCA
	Audio output	1ch RCA
	Alarm input	No
	Alarm output	No
	Network interface	RJ45 10M/100M Adaptive Ethernet port



Email: sales@foresight-systech.com www.foresight-systech.com

	PTZ control	One RS485; support multiple PTZ protocols
	USB	2 USB ports
	Hard disk	1 SATA(Each maximum support 4T)
	Wireless	3G、WIFI(expand via USB)
Other	Power	12V/2A
	dimension	255mm(length)* 225mm(width)* 60mm(height)