

# AHD HYBRID DVR



- + Support AHD and Analog cameras
- + Support VGA, HDMI 1080P full HD output;
- + Support Cloud technology, easy to achieve a variety of network penetration, one step to remote monitoring, getting rid of various complicated network settings, easy and simple to operate;
- + Support various mobile monitoring: (IOS, Windows Mobile, BlackBerry, Symbian, Android) .
- + Support multiple web browsers (IE、Chrome、Firefox、Safari);
- + Support more than 20 languages (English、Finnish, French, German, Greek, Italian, Japanese, Polish, Portuguese, Russian, Spanish, Thai, Chinese, Traditional Chinese, Turkish, etc.), no nation boundaries;
- + perfect protection circuit, unique triple watchdog function
- + Supporting web, CMS, center platform management software MYEYE, provide SDK development.

FST-AH88K5		
System	Main processor	Huawei Hass 3531
Video	video compression	H.264(High Profile);
	Encode	8*720P real-time
	Decode	8*720P real-time
	Multi-mode	Pure Analog: 8*720P; 8*AHD;
	input	Mixed: 4*720P (Analog) +4*720P (Network) ;
		Pure Network: 1*1080P+8*720P; 4*1080P; 20* AHD
Audio	Audio compression	G.711A
	Intercom	support
Recording and Playback	Record mode	Manual>alarm>motion detection>timing
	Playback Channels	8 (pure local input mode)
Storage and backup	Space occupation	960H: 12~20G/ day*channel
		720P: 20G~30G/ day*channel
		audio: 691.2M/ day*channel
	Backup mode	Network backup、USB HDD, USB writer、SATA writer
Interface	Video input	8 BNC
	Video output	1ch VGA,1ch HDMI
	Audio input	8ch RCA
	Audio output	1ch RCA
	Alarm input	16
	Alarm output	4



	Network interface	RJ45 10M/100M Adaptive Ethernet port
	PTZ control	One RS485, one RS232; support multiple PTZ protocols
	USB	2 USB ports
	Hard disk	8 SATA (Each maximum support 4T )
	Wireless	3G、WIFI(expand via USB)
Other	Power	DVR dedicated ATX Power Supply
	dimension	442mm(length)* 430mm(width)* 91mm(height)