

Outdoor dome camera



-  Vandalproof Dome
-  Weatherproof Rate: IP66
-  IR LED: 21EA ϕ 5
-  Lens: 2.8-12mm

| | | FST-ERM820- | FST-ERM620-C | FST-ERM720-C | |
|----------|-----------------------|---|---------------|---------------|--|
| CAMERA | Image Sensor | 1/3" DIS | | | |
| | Signal System | PAL/NTSC | | | |
| | Effective Pixels | 720(H)X480(V) | 728(H)X488(V) | 976(H)X496(V) | |
| | Min Illumination | 0.1Lux @ (F1.2,AGC ON),0 Lux with IR 0.14Lux @ (F1.4,AGC ON),0 Lux with IR | | | |
| | Shutter Time | 1/50(1/60)s to 1/100,000s | | | |
| | Lens | 2.8-12 mm @ F1.4 | | | |
| | Lens Mount | ϕ 14 | | | |
| | Day & Night | IR cut filter with auto switch | | | |
| | Horizontal Resolution | 600TVL | 70TVL | 1000TVL | |
| | Synchronization | Internal Synchronization | | | |
| | Video Output | 1Vp-p Composite Output (75 Ω /BNC) | | | |
| | S/N Ratio | More than 62 dB | | | |
| | BLC | On | | | |
| | OSD | WDR | D-WDR | -- | |
| | | Back Light | ON/OFF/HLC | -- | |
| Motion | | ON/OFF | -- | | |
| Privacy | | ON/OFF | -- | | |
| Language | | English/Chinese/Spanish/Russian/Japanese/Dutch/French/Portuguese | -- | | |
| General | Operating Conditions | -40 °C - 60 °C (-40 °F - 140 °F) Humidity 90% or less (non-condensing) | | | |
| | Power Supply | 12 V DC \pm 10% | | | |
| | Power Consumption | Max. 4 W(Max. 5 W with IR cut filter on) | | | |
| | Weather Proof | IP66 | | | |
| | IR Range | Approx 30 to 40 meters | | | |
| | Weight | 800G | | | |