



Outdoor dome camera



- ✚ Vandalproof Dome
- ✚ Weatherproof Rate: IP66
- ✚ IR LED: 30pcs EA ϕ 5
- ✚ Lens: 2.8-12mm(3MP)
- ✚ 3 Axis Bracket
- ✚ Complete OSD Menu
- ✚ Optional IR Cut Filter
- ✚ Optional AutoIris
- ✚ Optinal dual Voltage

FST-HD7920		
Image Sensor	1/3" SONY DOUBLE SCANN CCD (960H)	
TV system	PAL/NTSC	
Total Pixel	976(H) x 494(V) NTSC	
	976(H) x 582(V) PAL	
Horizontal Res.	700TVL	
Video Output	1.0V p-p (75 ohm, composite)	
Scanning System	2:1 Interlace	
Lens	2.8-12mm manual iris	
Minimum Illumination	Color: 0.1Lux@F1.2;	
	B/W: 0.08Lux@F1.2	
	0Lux(IR ON)	
S/N Ratio	>50 dB (AGC OFF)	
DNR	3-DNR	
OSD	WDR	WDR
	Back Light	OFF/BLC/HLC
	Motion Detection	ON/OFF
	Privacy	ON/OFF
	Sens-up	ON/OFF
	Language	English/Chinese/Spanish/Russian /Japanese/Dutch/French/Portuguese
Power Voltage	DC12V	
Operation Temp.	-10°C~50°C	
Net weight	1050g	