

2.4 Outdoor Megapixel IP Camera



- ✚ 3-Axis bracket
- ✚ IR LED: 24pcs EA ϕ 5
- ✚ Lens: 2.8-12mm
- ✚ External POE optional model FST-TID220-POE
- ✚ 2.4 Megapixel Resolution, 1920(H)*1080(V), 1080p
- ✚ Support ONVIF2.0

FST-TID220	
Camera	
ImageSensor	1/3" SONY 2.4MP CMOS Sensor IMX222
Mainprocessor	DM368(TIDaVinci™)
Resolution	1080P
EffectivePixels	1920(H)*1080(V)
TVSystem	PAL/NTSC
ElectronicShutterTime	Auto:PAL1/50-1/100,000Sec;NTSC1/60-1/100,000Sec
Mini Illumination	0.1 Lux (0 Lux, IR ON: CDS auto control)
IR LED	24 EA ϕ 5
Lens	2.8-12mm
S/NRatio	\geq 52dB
Day/Night	Color/ B&W (IR-CUT)
Compression	H.264/JPEG, Support back AVI format.
Image Config	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, BLC, FLK(Flicker Control)
Motion Detection	Support
Privacy Masking	3 Rectangular Zone
Recording Mode	NVR/NAS/CMS/Web
VideoOutput	Network
Network	
Ethernet	RJ-45(10/100Base-T)
Protocol	IPv4,HTTP,TCP/IP,FTP,NTP,RTSP,UDP,SMTP,DNS,DDNS
ONVIF	SupportONVIF2.0
VideoDelay	0.3s(WithintheLan)
DualStream	MainStream:1920*1080,1280*720SubStream:704*576,352*288
IEBrowser	IE6-11, Firefox, Chrome
SmartPhone	iPhone,iPad,Android,AndroidPad



General	
Housing	Indoor
IRCutFilter	YES
OperationTemperature	-10°C~+50°C RH95%Max
StorageTemperature	-20°C~+60°C RH95%Max
PowerSource	DC12V±10%,900mA