

IR bullet camera(fix lens)



- ✚ 3-Axis bracket
- ✚ Weatherproof Rate: IP66
- ✚ IR LED: 26pcs EA \$ 5
- ✚ Lens: 3.6/6mm
- ✚ Cable Protected through the bracket

| | | FST-YBM620-C | FST-YBM720-C | FST-YBM7220-C |
|------------------|-----------------------|--|---------------|---------------|
| CAMERA | Image Sensor | 1/3" DIS | | |
| | Signal System | PAL/NTSC | | |
| | Effective Pixels | 720(H)X480(V) | 728(H)X488(V) | 976(H)X496(V) |
| | Min Illumination | 0.1Lux @ (F1.2,AGC ON),0 Lux with IR | | |
| | | 0.14Lux @ (F1.4,AGC ON),0 Lux with IR | | |
| | Shutter Time | 1/50(1/60)s to 1/100,000s | | |
| | Lens | 3.6/6MM @ F1.4 | | |
| | Lens Mount | φ12 | | |
| | Day & Night | IR cut filter with auto switch | | |
| | Horizontal Resolution | 600TVL | 700TVL | 1000TVL |
| | Synchronization | Internal Synchronization | | |
| | Video Output | 1Vp-p Composite Output (75Ω/BNC) | | |
| | S/N Ratio | More than 62 dB | | |
| | BLC | On | | |
| | OSD | WDR | D-WDR | |
| Back Light | | ON/OFF/HLC | | -- |
| Motion Detection | | ON/OFF | | -- |
| Privacy | | ON/OFF | | -- |
| Language | | English/Chinese/Spanish/Russian/Japanese/Dutch/French/Portuguese | | -- |
| GENERAL | Operating Conditions | -40 °C - 60 °C (-40 °F - 140 °F) | | |
| | | Humidity 90% or less (non-condensing) | | |
| | Power Supply | 12 V DC±10% | | |
| | Power Consumption | Max. 4 W(Max. 5 W with IR cut filter on) | | |
| | Weather Proof | IP66 | | |
| | IR Range | Approx 25 to 30 meters | | |
| Weight | 300G | | | |