

1.3Megapixels High Speed Dome



- ✦ 1.3 Megapixel, 1/3" CMOS; 20x optical zoom;
- ✦ Support PSIA/ONVIF, convenient to connect to third
- ✦ Support four streamings, the Resolution and Frame R independently;
- ✦ PWM function, intelligent IR illumination & power consumption variable, dependant the zoom factor;
- ✦ IR distance 150M; English OSD menu
- ✦ Support ambient light detection, IR illumination on 1-selectable;
- ✦ *Dome ID, baud rate, communication protocol can be controlled;
- ✦ Supported Protocols: Pelco-D/P; Others on special request
- ✦ 7" total metal body construction, waterproof IP66;
- ✦ Optional, 4 alarm inputs and 2 alarm outputs.

FST-13C2M9

FST-13C2M9	
Camera module	
sensor	1/3" processive scan CMOS
Effective pixels	720P (1280x720)
Total pixel	1.3 Megapixels
Output Oixel	1280*720@60fps 1280*720@50fps
Lens	4.7±5%~94±5%mm
Iris	F1.6 - F2.7
View of Angle	H : 54.8° (W) ~ 3.4° (T) V : 41° (W) ~ 2.5° (T)
Min.illumination	Color:0.1Lux B/W:0.01Lux
D/N	IR Cut
WB	Manual/Auto
AGC	Manual/Auto
S/N Ratio	≥50dB
Dome	
Communications Protocol	TCP/IP, HTTP, FTP, RTSP, UPnP, DNS, NTP, RTP, UDP, IGMP
Storage (optional)	One SD card
Software Control	IE, CMS, Management Platform
Mobile View(optional)	Support Windows, Symbian, iPhone platform smartphone
Horizontal Rotation Speed	0.02 ~ 300°/s
Horizontal Rotation Range	0.02 ~ 160°/s
Tilt Rotation Speed	360°/s
Tilt Rotation Range	93°



Auto Flip	Horizontal 180°, Vertical 180°
Auto Control IR LED	PWM
A-B Scan	User programmable
A-B Scan Speed	1-9 levels setting available
Dwell Preset	2-60s interval available
Preset Points	220
Go to Preset Speed	01-64 levels available
Guard Tours	4 groups
Guard Points	Max.16 points, dwell time user selectable
PWR On Action	Memory/Pattern 1/Tour 1/360° scan/A-B scan/Preset 1-8/None
Park Time	1-60mins available
Pattern Scan	4 pcs
Pattern Scan Record	Max.15 minutes, max.512 commands
Time Scheduling Function	8 tasks
Communication Protocol	Pelco-D, Pelco-P
Baud Rate	9600bps
Operating Temperature	Indoor: 0°~ +40° Outdoor: -40°~ +60°
Operating Humidity	≤95% Non Condensing
Heater & Blower	Auto temperature control
Power	AC24V/3A
IR Illumination Distance	150M
Power Consumption	≤ 25W
Lightning Protection	Transient voltage 6000V
Compatible Camera	Chinese , Samsung,Sony
IR LED	10PCS\$20



Foresight

Foresight Systems Technology

**Email: sales@foresight-systech.com
www.foresight-systech.com**