

Pinhole board Camera



- ✚ High Effective Resolution, up to 650 TV Lines
- ✚ Metal housing and bracket
- ✚ High Class Menu Operation (OSD) on the camera cable optional
- ✚ Pinhole Lens, Optional 3.7mm, 2,8mm Fix



| | FST-246S620-PH | FST-242P20-PH |
|-------------------------|-----------------------------------|--------------------|
| Sensor | 1/3 SONY CCD | |
| SYSTEM | NTSC/PAL | |
| Synchronize | Internal | |
| Resolution | 650TVL | 420TVL |
| | 795(H)*596(V) 470K | 537(H)*597(V) 320K |
| S /N | ≥60dB | |
| Minimum | 0.1Lux F1.2 | |
| Gamma Correction | 0.45 | |
| AGC | +18dB Max | |
| White Balance Range | 2200~10000K | |
| OSD Menu (optional) | Available upon request | |
| Back Light Compensation | ON/OFF (for models with OSD menu) | |
| Electrical Shutter | 1/60(1/50)-1/120000sec | |
| Power Supply Voltage | DC12V | |
| Power Supply Current | <85mA (IR OFF) | |
| Lens | 3.7mm pin hole lens | |
| Operation Temperature | -10 to 50 | |
| Storage Temperature | -20 to 65 | |
| Operation Humidity | Within85%RH | |
| Certification | CE, FCC | |