



wireless GSM home alarm



- + 4 wire / 6 wireless zones
- + 6 groups of voice telephone No. 3 groups of telephone No. to send SMS
- + 1 group of NO, NC signal output
- + Telephone (cell phone) remote control set programme
- + 5.10s ISD message record automatically
- + Built-in human intelligent digital voice machine
- + 7. Alarm lock memory
- + Leave arm, At home arm, remote control arm
- + Wireless intelligent learning code, easy to operate
- + Cell phone (telephone) remote control arm, disarm, monitor the sound
- + Timely, delay, 24-hour, bypass zones
- + Remote control arm/disarm operate siren prompt can be set
- + E2PROM message protect, the message will not lost even if it's power off
- + Built-in NI-HI rechargeable battery, it can shift to spare battery if it's power off
- + AC, DC to be used, 24-hour continuous work
- + Alarm panel tamper, low voltage self-checking function

FST-LFGSMFDX	
Input voltage	DC9V-12V
Static currency	less than 55mA
Alarm currency	less than 450mA
wiress currency	315MHz or 433MHz (selectable)
GSM mode	900/1800/1900MHz
Built-in battery	NI-HI AAA*6 DC7.4V
Voice of siren	110dB
Humidity	40%~70%
Weight	2.5KG
Dimension of Metal Box	26.5 x 26 x 7.8 cm