



Mini Beams fence barrier



- ✚ 4 frequencies for option to offer an effective solution to mutual interference among each group of barriers.
- ✚ Bi-directional mutual-transmission operation way to avoid sunshine interference.
- ✚ AGC control circuit to confirm its normal operation in very severe environments such as wind, frost, rain, snow and fog etc.
- ✚ Hint of aiming status, more convenient and quick installation.
- ✚ Multi layers technical process on anti-thundering, water-proof and static-immunity.
- ✚ Qualified aluminum alloy housing, special and elegant appearance design.
- ✚ 360° for horizontal rotation, convenient for installation and usage.
- ✚ Military and industrial grade transmission, receiver works with non-spherical lens to get more stable operation and longer distance.
- ✚ Multi height and operation distances for option.
- ✚ Intelligent pet-immunity technology.
- ✚ It is fit for installation in terrace, windows, alley, warehouse, villa, military area and governmental offices etc.

	FST-MVF420 FST-MVF620	FST-MVF440 FST-MVF640	FST-MVF460 FST-MVF660
	FST-MVF820 FST-MVF1220	FST-MVF840 FST-MVF1240	FST-MVF860 FST-MVF1260
Distance	20m	40m	60m
Voltage	DC 13.8-24V AC 11-18V		
Alarm/Tamper Output	Alarm Relay contact output:NO and NC Tamper Contact output:NC contact rating:AC/DC30V 0.5A Max		
Operation Temperature	-25°C ~ +60°C		
Operation Humidity	5%---95%		
Optical Axis Adjustment	H: ±90° V: ±2°		
Tamper output	Normal close (NC) touching capability AV/DC 24V/0.5mA		