

Wi-Fi or Wired Night Vision Alarm IP camera



- ♣ Configure device through wired/wireless network.
- ♣ Support horizontal and vertical PTZ; control viewing angle freely.
- ♣ Support soundwave and wire configuration.
- Built-in MIC and speaker, support two-way talk.
- ♣ Support multiple RS433 alarming methods,magnetic door,bracelet etc.
- Support High/Standard/Flow definition switch.
- ♣ Support 64G local storage.
- Record file format: MP4.
- Support Android/IOS/Windows PC client remote view.
- ♣ Capable of seeing face clearly within 8m in daytime; 10m IR distance at night.



		FST-SOSR6
Camera	Image Sensor	1/4"CMOS
	Resolution	1280×720
	Pixel	1.0MP
	Compression	H.264/JPEG
	Frame Rate	25fps
	Bit Rate	64Kbps~8Mbps
	Min.Illumination	OLux(IR ON)
Lens	Lens Mount	M12
	Lens	3.6mm
		71°
	View Angle	
	Focus	Fixed
	Privacy Mask	4 Rectangle areas
	Exposure Control	Auto
	Gain Control	Auto
	White Balance	Auto
	Day & Night	IR cut filter with auto switch ,
		Support Color to Black
		Supports contrast, brightness,
Function	Video Adjust	saturation, sharpness adjustment
	Remote	System、Stream、User、Network Management
	Operation	System - Stream - Oser - Network Management
	Motion Detection	Support
	Alarm	E-mail、Client
	Voice Intercom	Support
	Local Storage	64G
PTZ	Rotation Angel	Horizon:355° Vertical:120°
	Preset	127
Control	Automatic Cruise	1 line
	Horizontal Scan	1 Line
Interface	Audio Input	1 Built-in MIC
	Audio Output	1 Built-in Speaker
	Net	1 RJ45 10M/100M adaptive interface
	Alarm In	1 CH
	Alarm Output	1 CH
	TF slot	1 standard TF card slot
	Reset	Restore to the factory settings
Network	Ethernet	10/100M Ethernet
	Wireless	WIFI
	Dual Stream	Support
	Protocol	HTTP,TCP/IP,ICMP,UDP,SMTP,FTP,DHCP,DNS,PPPOE



Email: sales@foresight-systech.com www.foresight-systech.com

	Transmission	Internal Cloudsee Protocol
	Browser	IE8+,Chrome18+,Firefox5.0+,Safari5.02+
	Connection	6 CH
	User Permission	Up to 13 users , Three level authority:
		Administrator 、 User 、 Visitor
General	Infrared Lamp	10 LED Lamps
	IR distance (m)	10m
	Best distance (m)	8m
	Temperature	-20°C∼55°C
	Humidity	10%~90%
	Power Supply	DC 5V
	Power	≦3.2W
	Material	White ABS+PC
	Size(W×H×D)(mm)	95×123×122
	Weight(g)	300
	Installation	Wall/Ceil/Desk Mounting